



impression[®] E350

TECHNICAL DATA

LED SOURCE

LED-Type LED 350W

Lifetime (hours) 20.000h

Color temperature 7500 Kelvin

CRI (Ra) 77

OPTICAL SYSTEM

Minimum zoom 8°

Maximum zoom 42°

Focus Motorized 2m - infinite

MOVEMENT

Resolution 16 bit

Pan 640°

Tilt 262°

CONTROL

Display Illuminated graphic LCD, intuitive touch
wheel control, self charging buffer battery,

Protocol ArtNet, DMX-512, RDM

Wireless Lumenradio CRMX DMX/RDM

EFFECTS

Dimmer 0-100% super smooth electronical dimming,
Multiple dimming curves, Flicker free

Shutter Max. 25Hz electronically

Effect wheel Interchangeable, rotating and indexable

Prism 8-way, variable slow to very fast rotation

Iris Yes

Gobo wheel 1 7 Gobos, rotatable and indexable,

Gobo wheel 2 10 fixed metal gobo's

Color temp. filter Variable CTC, mechanical, 2.500 - 8.000K

Color wheel 9 dichroic color filters, CTB, CTO

Color mixing CMY color mixing

Internal effects LED macro effects

CONNECTORS

Signal connection XLR 5-pin, XLR 3-pin, input & output

Power input Neutrik powerCON TRUE1

OPERATING CONDITIONS

Mains voltage 100-240 VAC / 50-60Hz

Power Watt@230V 550 Watt

Fuse 20mm T 8A

Max ambient temp. 45° C

Operating position Any

MOUNTING OPTIONS

Standing Removable baseplate with belt brackets

Hanging vertical M10 sockets for clamps and halfcouplers,
omegabackets (optional)

Safety wire attachm. 2 Eyelets

SHIPPING

Single fixture Cardboard

Tourpack 2-way incl. flightcase and halfcoupler

HOUSING COLORS

Standard colors Black

Optional Special colors on request

DIMENSIONS & WEIGHT

Length 472mm

Width 229mm

Height (head vert.) 650mm

Weight 25kg

*Profit is not the motivation...
the client is...*