



FUSION²

TECHNICAL DATA BAR10 / BAR20

LED SOURCE

LED-Type	15W RGBW Osram
Lifetime (hours)	20.000h
LED numbers	10 / 20
LED colors	RGBW

OPTICAL SYSTEM

Beam angle	6°
Diffuser filters	20°, 40°, 60° or 10°x60°

CONTROL

Protocol	USITT DMX-512
Control modes	8 DMX control modes ,stand alone
	Wireless DMX optional
	RDM
Display	OLED display with 4 buttons
Cooling	Convection cooled

CONNECTORS

Signal connection	XLR 5-pin, input & output IP65
Power input	Neutrik PowerCON TRUE1

OPERATING CONDITIONS

Mains voltage	100-240 VAC / 50-60Hz
Power Watt@230V	330 Watt
IP-rate	IP65
Max ambient temp.	45° C

MOUNTING OPTIONS

Rigging	2x M10, 2x Omegabacket, mount for safety wire, bracket for vertical dropping (optional)
Standing	2x stand with manual horizontal tilt, Stand for max. 2 units vertical (optional)

SHIPPING

Single fixture	Cardboard
Tourpack	Case for 4 Fusion2

DIMENSIONS & WEIGHT

Length	503mm/1006mm
Width	90mm
Height	181mm without stand 231mm with stand
Weight	12,5kg

