



# FUSION PAR FP7

TECHNICAL DATA PAR FP7	
<b>LED SOURCE</b>	
LED-Type	7 x RGBW Osram LED
Lifetime (hours)	20.000h
<b>OPTICAL SYSTEM</b>	
Beam angle	6°
	20°, 40°, 60° and 60 x 10° diffusion filter
	optional
<b>CONTROL</b>	
Protocol	USITT DMX-512
Control modes	6 DMX control modes ,stand alone mode
<b>FUNCTIONS</b>	
	High resolution dimmer 0 - 100%
	Selectable dimming curves
	Strobe with variable speed (max 20Hz)
	RGBW, 8 or 16 bit color mixing
	Seamless CTO, virtual colorwheel including
	whites (2700K, 3200K, 4200K, 5600K, 7200K
	and 8000K)

<b>CONNECTORS</b>	
Signal connection	XLR 5-pin, input & output IP65
Power input	Neutrik PowerCON TRUE1
<b>OPERATING CONDITIONS</b>	
Mains voltage	100-240 VAC / 50-60Hz
Power Watt@230V	220 Watt
IP-rate	IP65
Max ambient temp.	45° C
<b>MOUNTING OPTIONS</b>	
Rigging	1x hole with 12mm diameter for one point mount
	1x omegabrackets optional
	1x mount for safety wire
<b>SHIPPING</b>	
Single fixture	Cardboard
<b>DIMENSIONS &amp; WEIGHT</b>	
Width	237mm
Depth	166mm
Height	210mm without stand
	287mm with stand
Weight	7,7kg

