



impression[&] X4 BAR

TECHNICAL DATA KNV CUBE/ARC

LED SOURCE

LED-Type	1x 30W Hyper White, 16x 0,5W RGB
LED numbers	25 (5 x 5)

CONTROL

Control modes	Normal, Compressed, Pixelmapping
Display	Illuminated graphic LCD, Self charging buffer battery, Backlit buttons
Protocol	USITT, DMX-512
Cooling	Temp. controlled, overheating protection

CONNECTORS

Signal connection	etherCON, input & output
Power input	Neutrik Powercon TRUE1

OPERATING CONDITIONS

Mains voltage	100-240 VAC / 50-60Hz
Power Watt@230V	750W
Max ambient temp	40°
Operating position	any

IP-rate	IP54
EEC	A
EEL	0,218
Ec (kWh/1.000h)	742

MOUNTING OPTIONS

Mounting	Bracket for hanging /standing(CUBE)
	KNV connector (CUBE & ARC)

SHIPPING

Single fixture	Cardboard
Tourpack	CUBE: 6-way flightcase ; ARC: 4-way flightc.

HOUSING COLORS

Standard colors	Black
-----------------	-------

DIMENSIONS & WEIGHT

Length	250mm
Width	250mm
Height (head vert.)	250mm
Weight	9,3kg

